	50	'R.O.W. ————		
— 10'—	14'	ହ ┥ ┥ ────────────────────────	 10'	
4" TOPSOIL, GRADE, — FERTILIZE, LIME, SEED & MULCH	1'−0"	POINT OF APPLICATION OF GRADE	72	1 (MAX.)
1"/FT.	9" 3/8" PER FT.	9"	1"/FT.	
2:1 (MAX.) BITUMINOUS CONCRETE 1'-0"			BITUMINOUS CURBI	
CURBING				
	ATERIAL THICKNESS OR COMPACTED DEPTH	/ / / <u> </u>	NOUS CONCRETE SURFACE NOUS CONCRETE BINDER (SSED AGGREGATE BASE	
A TOP PERIOI MAY R OF BIT APPLIE	IDER COURSE IS LEFT AS COURSE FOR AN EXTENDED D, THE DIR OF PUBLIC WORKS REQUIRE THAT A TACK COAT TUMINOUS MATERIAL MAY BE ED BEFORE LAYING THE INOUS CONCRETE SURFACE	/ L8" GRAVEI	L BASE (GREATER DEPTH	IF REQUIRED)
COURS 3. SUBBA INCRE/	SE. ASE DEPTH SHALL BE 4. FOR CO ASED TO 18" WHERE LEDGE CONNEC	ONSTRUCTION MATERIAL STANDARDS, CTICUT, STANDARD SPECIFICATIONS FO	R ROADS, BRIDGES	
	IS ENCOUNTERED. AND INC	CIDENTAL CONSTRUCTION, FORM 813,	AS AMENDED.	
		SECTION LOCAL STREET	_	
	18' SH	ARED DRIVEWAY		
	EXISTING G	RADE '4" PER. FT.		
			////	
2-1/2" BITUMIN	NOUS CONCRETE OR MILLINGS	\ TOPSOIL. REP	NSUITABLE MATERIAL & LACE WITH COMPACTED	
2—1/2" BITUMIN	4" processed gravel 8" bank run gravel TYPICAL SHARED DE	TOPSOIL, REP BANK RUN G	LACE WITH COMPACTED RAVEL	
2-1/2" BITUMIN APPROVED BY THE LEDYARD PLANNING AN COMPLIANCE WITH THE REGULATIONS GOVI ALL IMPROVEMENTS SHALL BE COMPLETED CHAIRMAN OR SECRETARY LOT NUMBERS ASSIGNED BY THE ASSESSO ASSESSOR IWWC APPLICATION#	4" PROCESSED GRAVEL 8" BANK RUN GRAVEL TYPICAL SHARED DI NO NO NO NO NO NO NO NO NO NO NO NO NO	TOPSOIL, REP BANK RUN G DT TO SCALE	SECTION SECTION	STEEL POST WITH (2) 1/4 GALVANIZED BOLTS (1 TOP, 1 BOTTOM) JTE: GN TO BE INSTALLED IN
APPROVED BY THE LEDYARD PLANNING AN COMPLIANCE WITH THE REGULATIONS GOVI ALL IMPROVEMENTS SHALL BE COMPLETED CHAIRMAN OR SECRETARY LOT NUMBERS ASSIGNED BY THE ASSESSO	4" PROCESSED GRAVEL 8" BANK RUN GRAVEL TYPICAL SHARED DI NO	TOPSOIL, REP BANK RUN G DT TO SCALE	SECTION	STEEL POST WITH (2) 1/4 GALVANIZED BOLTS (1 TOP, 1 BOTTOM) JTE: GN TO BE INSTALLED IN
APPROVED BY THE LEDYARD PLANNING AN COMPLIANCE WITH THE REGULATIONS GOVI ALL IMPROVEMENTS SHALL BE COMPLETED CHAIRMAN OR SECRETARY LOT NUMBERS ASSIGNED BY THE ASSESSO ASSESSOR IWWC APPLICATION# 	4" PROCESSED GRAVEL 8" BANK RUN GRAVEL TYPICAL SHARED DI NO	TOPSOIL, REP BANK RUN G DT TO SCALE	SECTION SECTION	STEEL POST WITH (2) 1/4 GALVANIZED BOLTS (1 TOP, 1 BOTTOM) JTE: GN TO BE INSTALLED IN
APPROVED BY THE LEDYARD PLANNING AN COMPLIANCE WITH THE REGULATIONS GOV ALL IMPROVEMENTS SHALL BE COMPLETED CHAIRMAN OR SECRETARY LOT NUMBERS ASSIGNED BY THE ASSESSO ASSESSOR IWWC APPLICATION#	4" PROCESSED GRAVEL 8" BANK RUN GRAVEL TYPICAL SHARED DI NO	TOPSOIL, REP BANK RUN G AIVEWAY CROSS—S DT TO SCALE	SECTION SECTION OP SIGN TO SCALE	JTE:
APPROVED BY THE LEDYARD PLANNING AN COMPLIANCE WITH THE REGULATIONS GOV ALL IMPROVEMENTS SHALL BE COMPLETED CHAIRMAN OR SECRETARY LOT NUMBERS ASSIGNED BY THE ASSESSO ASSESSOR IWWC APPLICATION# APPROVED, NO PERMIT NECESSARY. (NO PERMIT NECESSARY. (4" PROCESSED GRAVEL 8" BANK RUN GRAVEL TYPICAL SHARED DI NO ND ZONING COMMISSION AS TO THE ERNING THE SUBDIVISION OF LAND. D BY DATE OR OR NOT WITHIN A REGULATED AREA; PROPOSED AT THIS TIME.) WORKS OR THE TOWN ENGINEER	STOP TOPSOIL, REP BANK RUN G RIVEWAY CROSS—S TO SCALE ST TO SCALE ST TO SCALE ST TO SCALE ST TO SCALE ST TO SCALE	SECTION SECTION OP SIGN TO SCALE	STEEL POST WITH (2) 1/4 GALVANIZED BOLTS (1 TOP, 1 BOTTOM) JTE: GON TO BE INSTALLED IN CCORDANCE WITH STATE CONNECTICUT D.O.T. STAN
APPROVED BY THE LEDYARD PLANNING AN COMPLIANCE WITH THE REGULATIONS GOV ALL IMPROVEMENTS SHALL BE COMPLETED CHAIRMAN OR SECRETARY LOT NUMBERS ASSIGNED BY THE ASSESSO ASSESSOR IWWC APPLICATION# 	4" PROCESSED GRAVEL 8" BANK RUN GRAVEL TYPICAL SHARED DI NO NO NO ND ZONING COMMISSION AS TO THE ERNING THE SUBDIVISION OF LAND. D BY DATE DATE OR	STOP TOPSOIL, REP BANK RUN G RIVEWAY CROSS—S TO SCALE ST TO SCALE ST TO SCALE ST TO SCALE ST TO SCALE ST TO SCALE	SECTION SECTION COP SIGN TO SCALE	STEEL POST WITH (2) 1/4 GALVANIZED BOLTS (1 TOP, 1 BOTTOM) JTE: GON TO BE INSTALLED IN CCORDANCE WITH STATE CONNECTICUT D.O.T. STAN CONNECTICUT D.O.T. STAN ECURE TO 1 1/2" GALVANIZ TEEL POST WITH (2) 1/4" ALVANIZED BOLTS

























