4 **(4)** 0 Θ 6 \odot Θ . W \odot 0 \Box 0 SANITARY ELEVATION DATA:

SANITARY INVERT AT SLAB: SANITARY DESIGN CRITERIA:

A. PROPOSED TWO BEDROOM HOME. NO TUBS GREATER THAN 100 GALLONS IN SIZE. <u>(5)</u> 4 \odot \ominus SANITARY DESIGN CRITERIA:

A. PROPOSED TWO BEDRO SANITARY ELEVATION DATA: SANITARY ELEVATION DATA:

(1) SANITARY INVERT AT SLAB: 100.50 © THIS DRAWING IS THE PROPERTY OF THE LAND SURVEYOR.

THIS PLAN AND REPRODUCTIONS, ADDITIONS OR REVISIONS OF

THIS PLAN ARE NOT VALID WITHOUT THE EMBOSSED SEAL AND

SIGNATURE OF THE LAND SURVEYOR WHO PREPARED THIS PLAN.

JOB# 24-010.DWG FBK#335 EFFECTIVE LEACHING AREA PROVIDED:

1 - ROW 16' 1' X 16' X 26.2 S.F./L.F. = 419.2 S.F

100% RESERVE AREA REQUIRED AND PROVIDED, SAME AS PRIMARY. EFFECTIVE LEACHING AREA REQUIRED PER CODE: 375 S.F.

GEOMATRIX GST 6236 SELECTED FOR PRIMARY SEPTIC SYSTEM DESIGN.

EFFECTIVE LEACHING AREA PROVIDED PER L.F. PER CODE: 26 S.F.

MINIMUM LENGTH OF TRENCH REQUIRED: 375 S.F./ 26.2 S.F./L.F.=14.4' EFFECTIVE LEACHING AREA REQUIRED PER CODE: 375 S.F.

GEOMATRIX GST 6236 SELECTED FOR PRIMARY SEPTIC SYSTEM DESIGN.

EFFECTIVE LEACHING AREA PROVIDED PER L.F. PER CODE: 26 S.F.

MINIMUM LENGTH OF TRENCH REQUIRED: 375 S.F./ 26.2 S.F./L.F.=14.4' EFFECTIVE LEACHING AREA PROVIDED:

1 — ROW 16' 1'X 16'X 26.2 S.F./L.F. = 419.2 S.F

100% RESERVE AREA REQUIRED AND PROVIDED, SAME AS PRIMARY DESIGN PERCOLATION RATE: 2.5 MIN./IN. MINIMUM LEACHING SYSTEM SPREAD: NOT APPLICABLE EFFECTIVE LEACHING AREA PROVIDED:

1 - ROW 16' 1' X 16' X 26.2 S.F./L.F. = 419.2 S.F

100% RESERVE AREA REQUIRED AND PROVIDED, SAME AS PRIMARY. MINIMUM LEACHING SYSTEM SPREAD: NOT APPLICABLE "D" BOX INVERT IN: 93.20 INVERT OUT: 93.00 EFFECTIVE LEACHING AREA REQUIRED PER CODE: 375 S.F. DESIGN PERCOLATION RATE: 2 MIN./IN. DESIGN PERCOLATION RATE: 3 MIN./IN. 1000 GALLON TWO COMPARTMENT SEPTIC TANK REQUIRED BY CODE AND PROVIDED. MINIMUM LEACHING SYSTEM SPREAD: NOT APPLICABLE 1000 GALLON TWO COMPARTMENT SEPTIC TANK REQUIRED BY CODE AND PROVIDED. "D" BOX INVERT IN: 96.20 INVERT OUT: 96.00 1000 GALLON TWO COMPARTMENT SEPTIC TANK REQUIRED BY CODE AND PROVIDED. "D" BOX INVERT IN: 99.20 INVERT OUT: 99.00 16' LONG GEOMATRIX GST 6236 DIST PIPE INV.: 93.00 BOTTOM OF UNIT ELEV.: 90.00 11'-4" DIA. SCHEDULE 40 ASTM D1785 OR EQUAL PIPE (MIN. SLOPE = 1/4" PER FT.) GEOMATRIX GST 6236 SELECTED FOR PRIMARY SEPTIC SYSTEM DESIGN.

MINIMUM LENGTH OF TRENCH REQUIRED: 375 S.F./ 26.2 S.F./L.F.=14.4' 1000 GALLON TWO COMPARTMENT SEPTIC TANK INVERT IN: 99.75
INVERT OUT: 99.50
6' - 4" DIA. SDR 35 PVC PIPE 1000 GALLON TWO COMPARTMENT SEPTIC TANK INVERT IN: 93.75 INVERT OUT: 93.50
6' - 4" DIA. SDR 35 PVC PIPE 16' LONG GEOMATRIX GST 6236 DIST PIPE INV.: 96.00 BOTTOM OF UNIT ELEV.: 93.00 1000 GALLON TWO COMPARTMENT SEPTIC TANK INVERT IN: 96.75
INVERT OUT: 96.50
6' - 4" DIA. SDR 35 PVC PIPE 11'-4" DIA. SCHEDULE 40 ASTM D1785 OR EQUAL PIPE (MIN. SLOPE = 1/4" PER FT.) 11'-4" DIA. SCHEDULE 40 ASTM D1785 OR EQUAL PIPE (MIN. SLOPE = 1/4" PER FT.) SANITARY INVERT AT SLAB: 97.10 16' LONG GEOMATRIX GST 6236 DIST PIPE INV.: 99.00 BOTTOM OF UNIT ELEV.: 96.00 TWO BEDROOM HOME. NO TUBS GREATER THAN 100 GALLONS BEDROOM HOME. NO TUBS GREATER THAN 100 GALLONS 95.50 SANITARY DESIGN CRITERIA: ANY FILL MATERIAL ENCOUNTERED REPLACED WITH SELECT FILL.

A. PROPOSED TWO BEDROOM HOME. NO TUBS GREATER THAN 1 IN SIZE. <u></u> 0 <u></u> (<u>N</u> **(4**) \odot **(4**) \odot \odot Θ **(4**) \odot 0 Θ $_{\cdot}^{\varpi}$ SANITARY ELEVATION DATA:

(1) SANITARY INVERT AT SLAB: SANITARY ELEVATION DATA:

(1) SANITARY INVERT AT SLAB: <u>(5)</u> D. SANITARY DESIGN CRITERIA:

A. PROPOSED TWO BEDROOM HOME. NO TUBS GREATER THAN IN SIZE. SANITARY ELEVATION DATA: EFFECTIVE LEACHING AREA PROVIDED:

1 - ROW 16' 1' X 16' X 26.2 S.F./L.F. = 419.2 S.F

100% RESERVE AREA REQUIRED AND PROVIDED, SAME AS PF EFFECTIVE LEACHING AREA REQUIRED PER CODE: 375 S.F.

GEOMATRIX GST 6236 SELECTED FOR PRIMARY SEPTIC SYSTEM DESIGN.

EFFECTIVE LEACHING AREA PROVIDED PER L.F. PER CODE: 26 S.F.

MINIMUM LENGTH OF TRENCH REQUIRED: 375 S.F./ 26.2 S.F./L.F.=14.4' EFFECTIVE LEACHING AREA PROVIDED:

1 - ROW 16' 1' X 16' X 26.2 S.F./L.F. = 419.2 S.F.

100% RESERVE AREA REQUIRED AND PROVIDED, SAME AS PROVIDED. EFFECTIVE LEACHING AREA REQUIRED PER CODE: 375 S.F.

GEOMATRIX GST 6236 SELECTED FOR PRIMARY SEPTIC SYSTEM DESIGN.

EFFECTIVE LEACHING AREA PROVIDED PER L.F. PER CODE: 26 S.F.

MINIMUM LENGTH OF TRENCH REQUIRED: 375 S.F./ 26.2 S.F./L.F.=14.4' MINIMUM LEACHING SYSTEM SPREAD: NOT APPLICABLE MINIMUM LEACHING SYSTEM SPREAD: NOT APPLICABLE 1000 GALLON TWO COMPARTMENT SEPTIC TANK REQUIRED BY CODE AND PROVIDED. DESIGN PERCOLATION RATE: 2 MIN./IN. 1000 GALLON TWO COMPARTMENT SEPTIC TANK REQUIRED BY CODE AND PROVIDED. DESIGN PERCOLATION RATE: EFFECTIVE LEACHING AREA REQUIRED PER CODE: 375 S.F. DESIGN PERCOLATION RATE: 7 MIN./IN.

MINIMUM LEACHING SYSTEM SPREAD: NOT APPLICABLE EFFECTIVE LEACHING AREA PROVIDED:

1 - ROW 16' 1' X 16' X 26.2 S.F./L.F. = 419.2 S.F

100% RESERVE AREA REQUIRED AND PROVIDED, SAME AS "D" BOX INVERT IN: 89.20 INVERT OUT: 89.00 "D" BOX
INVERT IN: 90.20
INVERT OUT: 90.00 "D" BOX INVERT IN: 94.40 INVERT OUT: 94.20 1000 GALLON TWO COMPARTMENT SEPTIC TANK REQUIRED PROVIDED. 16' LONG GEOMATRIX GST 6236 DIST PIPE INV.: 90.00 BOTTOM OF UNIT ELEV.: 87.00 1000 GALLON TWO COMPARTMENT SEPTIC INVERT IN: 90.75
INVERT OUT: 90.50
6' - 4" DIA. SDR 35 PVC PIPE GEOMATRIX GST 6236 SELECTED FOR PRIMARY SEPTIC SYSEFFECTIVE LEACHING AREA PROVIDED PER L.F. PER CODE: MINIMUM LENGTH OF TRENCH REQUIRED: 375 S.F./ 26.2 16' LONG GEOMATRIX GST 6236 DIST PIPE INV.: 89.00 BOTTOM OF UNIT ELEV.: 86.00 1000 GALLON TWO COMPARTMENT SEPTIC TANK INVERT IN: 89.75
INVERT OUT: 89.50
6' - 4" DIA. SDR 35 PVC PIPE 11'-4" DIA. SCHEDULE 40 ASTM D1785 OR EQUAL PIPE (MIN. SLOPE = 1/4" PER FT.) 11'-4" DIA. SCHEDULE 40 ASTM D1785 OR EQUAL PIPE (MIN. SLOPE = 1/4" PER FT.) 18'-4" DIA. SCHEDULE 40 ASTM D1785 OR EQUAL (MIN. SLOPE = 1/4" PER FT.) 16' LONG GEOMATRIX GST 6236 DIST PIPE INV.: 94.20 BOTTOM OF UNIT ELEV.: 91.20 1000 GALLON TWO COMPARTMENT SEPTIC TANK INVERT IN: 94.95 INVERT OUT: 94.70
5' - 4" DIA. SDR 35 PVC PIPE SANITARY INVERT AT SLAB: OOM HOME. NO TUBS GREATER THAN GST 6236 91.50 93.50 95.50 DIET TER & GARDNER

VID SURVEYORS • PLANNERS

1641 ROUTE 12

P.O. BOX 335 'STEM DESIGN. :: 26 S.F. S.F./L.F.=14.4' BY CODE AND 100 GALLONS 100 GALLONS SHALL BE S FERRY, CT. 06335 860) 464-7455 TER.GARDNER@YAHOO.C 0 0 Θ \odot SANITARY DESIGN CRITERIA:

A. PROPOSED TWO BEDRO SANITARY ELEVATION DATA:

(1) SANITARY INVERT AT SLAB: **4** 0 **6** <u>(5</u> Θ Θ SANITARY DESIGN CRITERIA:

A. PROPOSED TWO BEDROOM HOME. NO TUBS GREATER THAN 100 GALLONS SANITARY ELEVATION DATA: EFFECTIVE LEACHING AREA PROVIDED:
1 - ROW 16' 1' X 16' X 26.2 S.F./L.F. = 419.2 S.F
100% RESERVE AREA REQUIRED AND PROVIDED, SAME AS PRIMARY. EFFECTIVE LEACHING AREA REQUIRED PER CODE: MINIMUM LEACHING SYSTEM SPREAD: NOT APPLICABLE 1000 GALLON TWO COMPARTMENT SEPTIC TANK REQUIRED BY CODE AND PROVIDED. EFFECTIVE LEACHING AREA PROVIDED:

1 - ROW 16' 1' X 16' X 26.2 S.F./L.F. = 419.2 S.F.

100% RESERVE AREA REQUIRED AND PROVIDED, SAME AS PRIMARY. EFFECTIVE LEACHING AREA REQUIRED PER CODE: 1000 GALLON TWO COMPARTMENT INVERT IN: 89.17 INVERT OUT: 88.92 6' - 4" DIA. SDR 35 PVC PIPE MINIMUM LEACHING SYSTEM SPREAD: NOT APPLICABLE EFFECTIVE LEACHING AREA PROVIDED:

1 - ROW 16' 1' X 16' X 26.2 S.F./L.F.

100% RESERVE AREA REQUIRED AND PROVIDE "D" BOX
INVERT IN: 88.62
INVERT OUT: 88.42 TARY ELEVATION DATA: DESIGN PERCOLATION RATE: 1000 GALLON TWO COMPARTMENT SEPTIC TANK REQUIRED BY CODE AND PROVIDED. "D" BOX INVERT IN: 90.20 INVERT OUT: 90.00 1000 GALLON TWO COMPARTMENT SEPTIC TANK INVERT IN: 89.75
INVERT OUT: 89.50
6' - 4" DIA. SDR 35 PVC PIPE EFFECTIVE LEACHING DESIGN PERCOLATION RATE: 3 MIN./IN. 11'-4" DIA. SCHEDULE 40 ASTM D1785 OR EQUAL (MIN. SLOPE = 1/4" PER FT.) SANITARY INVERT AT SLAB: 18'-4" DIA. SCHEDULE 40 ASTM D1785 (MIN. SLOPE = 1/4" PER FT.) SANITARY INVERT AT SLAB: 1000 GALLON TWO COMPARTMENT SEPTIC TANK REQUIRED BY CODE AND PROVIDED. 16' LONG GEOMATRIX GST 6236 DIST PIPE INV.: 88.42 BOTTOM OF UNIT ELEV.: 85.42 11'-4" DIA. SCHEDULE 40 ASTM D1785 OR EQUAL (MIN. SLOPE = 1/4" PER FT.) 6' LONG GEOMATRIX GST 6236 DIST PIPE INV.: 89.00 30TTOM OF UNIT ELEV.: 86.00 1000 GALLON TWO COMPARTMENT SEPTIC TANK INVERT IN: 89.75
INVERT OUT: 89.50
6' - 4" DIA. SDR 35 PVC PIPE 16' LONG GEOMATRIX GST 6236 DIST PIPE INV.: 89.00 BOTTOM OF UNIT ELEV.: 86.00 OMATRIX GST 6236 SELECTED FOR PRIMARY SEPTIC SYSTEM DESIGN.
FECTIVE LEACHING AREA PROVIDED PER L.F. PER CODE: 26 S.F.
INIMUM LENGTH OF TRENCH REQUIRED: 375 S.F./ 26.2 S.F./L.F.=14.4' INIMUM LEACHING SYSTEM SPREAD: NOT APPLICABLE GN PERCOLATION RATE: 5 MIN./IN. " BOX IVERT IN: 89.20 IVERT OUT: 89.00 MATRIX GST 6236 SELECTED FOR PRIMARY SEPTIC SYSTEM :ECTIVE LEACHING AREA PROVIDED PER L.F. PER CODE: 2 TRIX GST 6236 SELECTED FOR PRIMARY SEPTIC SYSTEM DESIGN. TIVE LEACHING AREA PROVIDED PER L.F. PER CODE: 26 S.F. JM LENGTH OF TRENCH REQUIRED: 375 S.F./ 26.2 S.F./L.F.=14.4' TWO BEDROOM HOME. NO TUBS GREATER THAN 100 GALLONS COMPARTMENT SEPTIC OOM HOME. NO TUBS GREATER THAN 100 AREA REQUIRED PER CODE: 93.00 89.75 2 MIN./IN. 375 S.F. 375 S.F. 375 S.F. TEMPORARY CONSTRUCTION ENTRANCE Θ SANITARY DESIGN CRITERIA:

A. PROPOSED TWO BEDRO SANITARY ELEVATION DATA:

SANITARY INVERT AT SLAB: 93.95 EFFECTIVE LEACHING AREA PROVIDED:

1 - ROW 16' 1' X 16' X 26.2 S.F./L.F. = 419.2 S.F

100% RESERVE AREA REQUIRED AND PROVIDED, SAME AS PRIMARY EFFECTIVE LEACHING AREA REQUIRED PER CODE: MINIMUM LEACHING SYSTEM SPREAD: 1000 GALLON TWO COMPARTMENT SEPTIC TANK REQUIRED BY CODE PROVIDED. DESIGN PERCOLATION RATE: "D" BOX INVERT IN: 91.37 INVERT OUT: 91.17 1000 GALLON TWO COMPARTMENT SEPTIC TANK INVERT IN: 91.95 INVERT OUT: 91.67
4' - 4" DIA. SDR 35 PVC PIPE 17'-4" DIA. SCHEDULE 40 ASTM D1785 OR EQUAL (MIN. SLOPE = 1/4" PER FT.) 16' LONG GEOMATRIX GST 6236 DIST PIPE INV.: 91.17 BOTTOM OF UNIT ELEV.: 88.17 FILTER FABRIC MATRIX GST 6236 SELECTED FOR PRIMARY SEPTIC SYSTEM DESIGN. ECTIVE LEACHING AREA PROVIDED PER L.F. PER CODE: 26 S.F. MUM LENGTH OF TRENCH REQUIRED: 375 S.F./ 26.2 S.F./L.F.=14.4' *H= 6" (GST6206)
12" (GST6212)
18" (GST6218)
24" (GST6224)
30" (GST6230)
36" (GST6236) ASTM C—33 Sand (or approved equivilant) ;" min. I.D., ASTM D—3034, SDR 35 pipe for gravity applications 75" min. I.D., ASTM D—2665, SCH 40 PVC pipe for pressure plications GEOMATRIX GST" LEACHING SYSTEM Finished Grade shall be pitched to sheet stormwater away from system *P= 2"-5.5"

*3" min. I.D., ASTM D-3034, SDR 35 pipe for gravity application 0.75" min. I.D., ASTM D-2665, SCH 40 PVC pipe for pressure applications 2.5 MIN./IN GEOMATRIX Cover material depth shall be >6 and shall be uniform over system NOT APPLICABLE GST " LEACHING FILTER FILTER FABRIC ATTACH FILTER FABRIC TO THE WIRE FENCING & EXTEND IT INTO THE TRENCH. OSTS & EXCAVATE

6" TRENCH. SET

DOWNSLOPE. ANGLE

PE FOR STABILITY

F—CLEANING. SYSTEM AND \leq FABRIC SEDIMENT BARRIER #6 DEVELOPMENT/AFFORDABLE MOBILE 1. MAINTAIN ALL SEDIMENT AND EROSION CONTROL FACILITIES UNTIL ALL AREAS HAVE BEEN STABILIZED.

2. LIMITS OF DISTURBANCE AND EROSION AND SEDIMENT CONTROL MEASURES ARE TO BE CONSIDERED AS TYPICAL MINIMUM STANDARDS. THE GENERAL CONTRACTOR WILL BE RESPONSIBLE FOR INSTALLING AND MAINTENANCE OF EROSION AND SEDIMENT CONTROL AND FOR IMPLEMENTING ADDITIONAL MEASURES AS SITE CONDITIONS WARRANT.

3. SLOPES IN HIGH MAINTENANCE AREAS SHALL NOT EXCEED 3:1 (H: V).

4. NO DRIVEWAY SHALL BE GREATER THAN 15% SLOPE AT ANY POINT. ANY DRIVEWAY HAVING A GRADE OF 8% OR MORE, BUT NOT EXCEEDING 15%, SHALL BE PAVED FOR THAT PORTION OF DRIVEWAY THAT EXCEEDS 8%. USE A TEMPORARY VEGETATION COVER OF ANNUAL RYE GRASS AT A RATE OF 1.0 lbs./1000 S.F. APPLY 10-10-10 FERTILIZER, OR EQUIVALENT, AT A RATE OF 7.5 lbs./1000 S.F. AND LIMESTONE AT A RATE OF 90 lbs./1000 S.F. APPLY STRAW OR HAY MULCH AT A RATE OF 70 lbs./1000 S.F. SHALL BE IN ACCORDANCE WITH THE STATE OF CONNECTICUT GUIDELINES FOR EROSION AND SEDIMENT CONTROL DATED MARCH 2024.
THIS PLAN HAS BEEN DEVELOPED TO MINIMIZE EROSION AND SEDIMENTATION AND REDUCE 1 IMPACT OF STORM WATER RUNOFF DURING CONSTRUCTION USING ENGINEERING PRINCIPALS DETAILED IN THE CONNECTICUT GUIDELINES FOR SOIL AND EROSION AND SEDIMENT CONTROL SEED BED PREPARATION: FINE GRADE AND RAKE SOIL SURFACE TO REMOVE STONES LARGER THAN 2" IN DIAMETER. APPLY LIMESTONE AT A RATE OF 90 lbs./1000 S.F. FERTILIZE WITH 10—10—10, OR EQUIVALENT, AT A RATE OF 7.5 lbs./1000 S.F. WORK LIMESTONE AND FERTILIZER NTO SOIL UNIFORMLY TO A DEPTH OF 4" WITH A HARROW OR EQUIVALENT. SEED APPLICATION: APPLY LAWN SEED BY HAND, CYCLONE SEEDER OR HYDROSEEDER. LIGHTLY DRAG OR ROLL THE SEED SURFACE TO COVER SEED. SEEDING SHOULD BE DONE BETWEEN APRIL 15 AND JUNE 15 OR BETWEEN AUGUST 15 AND SEPTEMBER 30. IF SEEDING CANNOT BE DONE DURING THESE TIMES, REPEAT MULCHING PROCEDURE BELOW UNTIL SEEDING CAN TAKE PLACE. NOTE: IF HYDROSEEDER SUSED, INCREASE SEED MIXTURE BY 10%. MULCHING: IMMEDIATELY FOLLOWING SEEDING, MULCH THE SEEDED SURFACE WITH STRAW OR HAY AT A RATE OF 70 lbs./1000 S.F. SPREAD MULCH ARROW. PERMANENT SEEDING INSPECT SEDIMENT BARRIERS AFTER EACH STORM EVENT AND REPAIR OR REPLACE AS NECESSARY. CLEAN OUT OF ACCUMULATED SEDIMENT IS NECESSARY IF 1/2 OF THE ORIGINAL HEIGHT OF THE BARRIER BECOMES FILLED IN WITH SEDIMENT. MAINTENANCE THIS PROJECT IS FOR THE DEVELOPMENT OF 10 MOBILE THERE ARE INLAND WETLANDS ON THIS PROPERTY. MARK COEN 860-608-7181 WILL SERVE AS CONTACT PERSON FOR IMPLEMENTING SEDIMENT CONTROL MEASURES ON THIS PLAN. THE ACCOMPANYING PLANS PROVIDE THE FOLLOWING OF THIS PLAN: STAKEOUT LIMITS OF CONSTRUCTION FOR THE DRIVEWAYS, HOMES AND SEINSTALL SEDIMENTATION CONTROL BARRIERS AS SHOWN ON THE PLAN.
REMOVE EXISTING VEGETATION AND TOPSOIL WITHIN THE LIMITS OF CONSTISTOCKPILE TOPSOIL AS SHOWN ON THE PLAN.
ROUGH GRADE THE DRIVEWAYS AND HOUSE AREAS.
INSTALL/CONNECT UTILITIES
FOLLOWING CONSTRUCTION OF THE HOMES, FINISH GRADE ALL DISTURBED LOAM AND SEED ALL DISTURBED AREAS. BY CHAIRMAN OR SECRETARY OF THE COMMISSION APPROVED BY THE LEDYARD PLANNING AND ZONING COMMISSION ON: DEVELOPMENT EXPIRATION DATE:
SOIL EROSION & SEDIMENT CONTROL PLAN CERTIFIED VOTE OF THE COMMISSION. EROSION ANTICIPATED THAT CONSTRUCTION WILL COMMENCE IN ORARY SEEDING FINISHED GRADES TO BE ACHIEVED LOCATION OF SEDIMENT CONTROL BARRIERS CONSTRUCTION SEQUENCE AND DETAILS SANITARY SANITARY DESIGN CRITERIA, SANITARY ELEVATION DATA, PARCEL LEDYARD, EROSION AND MANUFACTURED CHRISTY CONTROL **0** APPLICANT/OWNER SEDIMENTATION

MITH THE STATE OF CONNECT PLAN AND MARCH 2024

REVISED: APRIL 11, 2024

REVISED: JUNE 10, 2024 DONCO, NING ID: AND PER ₽ZU CONNECTICUT DETAILS SHOWING 1 0 0 HILL NARRATIVE HIGHWAY LLC CONTROL C.G.SSEDIMENT

SEWAGE DISPOSAL

SYSTEMS.

PLAN

품

1160

159

ROAD

HOME

PARK

800

30g

HOUSING